



① 规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC500 V.60 Sec.100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V(50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A — B B — C C — D	王光云	06-06-14
	D — C C — B B — A		
负荷寿命 Operating Life With Load	200±100 300±150 400±150	赖立辉	11 JUL 98

7	钢珠	STEEL BALL	STEEL	2	NATURAL
6	弹簧	SPRING	STEEL	1	NATURAL
5	端子	TERMINAL	C2680R①	20	Ag PLATED
4	基板	TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片	CONTACT	C5210R①	4	Ag CLAD
2	胶柄	KNOB	P O M	1	G 4 - 15
1	铁壳	FRAME	S P C C	1	Ni PLATED
序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	

A01	ADD: 规格 Specifications 见 ①	王光云	06-06-14
	C2680R-EH → C2680R 见 ①		
	C5210R-EH/Ag CLAD → C5210R 见 ①		
01		赖立辉	11 JUL 98
标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SLIDE SWITCH		ITEM NO	SS-44D04-G	
UNDER 1	± 0.10	DRAWN	王光云	06-06-14	VERSION	A01	PAGE 1 OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-06-14	SCALE		UNIT mm
OVER 10	± 0.50	APPROVED	高洪	06-06-15	PROJECTION		

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.